



## OG8202/C/N - Lincat Opus 800 Natural Gas Counter-top Griddle - Chrome Plate - W 900 mm - 23.0 kW

Designed for quality cooking at speed, the Opus 800 Gas Chrome Griddle heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system.

- ✔ Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- ✔ Convenient piezo ignition and pilot Burners for stand-by operation
- ✔ Transfers heat to food more efficiently than a standard griddle
- ✔ Flame failure protection
- ✔ Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously

### Specifications

#### Summary

<b>Brand</b>	Lincat
<b>Range</b>	Opus 800
<b>Power Type</b>	Gas
<b>Gas Type</b>	Natural Gas
<b>Unit Type</b>	Counter-top
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105102724

#### Power and Performance

<b>BTU per Hour</b>	78,476
<b>Total Power kW</b>	23.0
<b>Temperature Range °C</b>	90-280
<b>Cooking Area (Width x Depth) mm</b>	890 x 600
<b>Temperature Control</b>	Mechanical

#### Key Specifications

<b>Number of Heat Zones</b>	2
<b>Grill Plate Surface Type</b>	Smooth
<b>Grill Plate Material</b>	Chrome

#### Capacity

<b>Product Output per Hour</b>	160 x 225g [8oz] steaks [chilled]
--------------------------------	-----------------------------------

#### Weights and Dimensions

<b>Unit Height (External) mm</b>	532
<b>Unit Width (External) mm</b>	900
<b>Unit Depth (External) mm</b>	800
<b>Net Weight Kg</b>	108

#### Supply Connections

<b>Requires Installation</b>	Yes
<b>Requires Electrical Supply</b>	No
<b>Gas Connection BSP</b>	1/2"
<b>Gas Consumption at full rate Natural m<sup>3</sup> per Hour</b>	2.19
<b>Gas Pressure Natural mbar</b>	20.0
<b>Total heat input at full rate Natural kW</b>	23
<b>Total heat input at full rate Natural BTU per hour</b>	23




**Shipping**

<b>Packed Weight Kg</b>	118.8
<b>Packed Height cm</b>	63
<b>Packed Width cm</b>	100
<b>Packed Depth cm</b>	85

**Available Accessories**

<b>OA8914</b>	Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
<b>OA8914/C</b>	Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
<b>OA8973</b>	Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm
<b>OA8973/C</b>	Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm

**Technical Picture**





**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm