



## YF62281/G500 - FriFri Basic+ 622 Electric Free- standing Twin Tank Fryer - 2 Baskets - W 600 mm - 2 x 15.0 kW

High-performance frying has never been as easy as it is with the FriFri Twin Tank 2 x 15kW Basic+ 622 Free Standing Fryer.

- ✔ Superb temperature control for consistently excellent results. Highly responsive digital electronic control able to maintain oil to +/-1 °C of the temperature selected
- ✔ Vertically coiled element for greater surface contact with oil, delivering fast recovery and preventing oil from scorching and degrading
- ✔ Twin tanks offer the versatility to cook different foods simultaneously and optional twin pumps help cater for special dietary requirements
- ✔ Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri<sup>®</sup> integrated oil pump and filtration system, increases efficiency, convenience and safety while extending oil life and saving you money
- ✔ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning

### Specifications

#### Summary

<b>Brand</b>	FriFri
<b>Range</b>	Basic+
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105117902

#### Power and Performance

<b>Total Power kW</b>	2 x 15.0
<b>Temperature Range °C</b>	60-190
<b>IP Rating</b>	IP25
<b>Temperature Control</b>	Electronic

#### Key Specifications

<b>Number of Baskets</b>	2
<b>Number of Tanks</b>	2
<b>Gravity Filtration</b>	Yes
<b>Pumped Filtration</b>	No
<b>Drain Location</b>	Through the body

#### Capacity

<b>Product Output per Hour</b>	2 x 32kg fries - 7mm [frozen]
<b>Capacity Litres</b>	2 x 12.5-14.5

#### Weights and Dimensions

<b>Unit Height (External) mm</b>	990
<b>Unit Width (External) mm</b>	600
<b>Unit Depth (External) mm</b>	650
<b>Net Weight Kg</b>	96

#### Supply Connections

<b>Requires Installation</b>	Yes
<b>Requires Electrical Supply</b>	Yes
<b>UK 3 Pin Plug</b>	No
<b>Requires Hardwiring</b>	Yes
<b>Electrical Supply Rating Watts</b>	2 x 15,000
<b>Three Phase Amps</b>	L1=2 x 21.7; L2=2 x 21.7; L3=2 x 21.7
<b>Three Phase Voltage</b>	400
<b>Number of Supply Cables</b>	2

## Shipping

<b>Packed Weight Kg</b>	105.6
<b>Packed Height cm</b>	113
<b>Packed Width cm</b>	79
<b>Packed Depth cm</b>	72

## Available Options

### Oil Pump

<b>OP1</b>	1 Oil Pump
<b>OP2</b>	2 Oil Pumps

### Baskets

<b>622_2_BASKETS</b>	2 Baskets
<b>622_3_BASKETS</b>	3 Baskets
<b>622_4_BASKETS</b>	4 Baskets

### Legs/Castors

<b>OC200</b>	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]
<b>OC400</b>	OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]



#### Lincat Limited

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



#### Customer Care

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

#### Export Customers

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

#### Opening Hours

**Monday – Friday:**  
8.30am – 5pm