



YF62271/G500 - FriFri Basic+ 622 Electric Free- standing Twin Tank Fryer - 2 Baskets - W 600 mm - 2 x 11.4 kW

High-performance frying has never been as easy as it is with the FriFri Twin Tank 2 x 11.4kW Basic+ 622 Free Standing Fryer.

- ✓ Superb temperature control for consistently excellent results. Highly responsive digital electronic control able to maintain oil to $\pm 1^{\circ}\text{C}$ of the temperature selected
- ✓ Vertically coiled element for greater surface contact with oil, delivering fast recovery and preventing oil from scorching and degrading
- ✓ Twin tanks offer the versatility to cook different foods simultaneously and optional twin pumps help cater for special dietary requirements
- ✓ Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri[®] integrated oil pump and filtration system, increases efficiency, convenience and safety while extending oil life and saving you money
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning

Specifications

Summary

Brand	FriFri
Range	Basic+
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour Warranty
Export Warranty	Contact your local dealer
GTIN	5056105117896

Power and Performance

Total Power kW	2 x 11.4
Temperature Range $^{\circ}\text{C}$	60-190
IP Rating	IP25
Temperature Control	Electronic

Key Specifications

Number of Baskets	2
Number of Tanks	2
Gravity Filtration	Yes
Pumped Filtration	No
Drain Location	Through the body

Capacity

Product Output per Hour	2 x 28.5kg fries - 7mm [frozen]
Capacity Litres	2 x 12.5-14.5

Weights and Dimensions

Unit Height (External) mm	990
Unit Width (External) mm	600
Unit Depth (External) mm	650
Net Weight Kg	96

Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	2 x 11,400
Three Phase Amps	L1=2 x 16.5; L2=2 x 16.5; L3=2 x 16.5
Three Phase Voltage	400
Number of Supply Cables	2

Shipping

Packed Weight Kg	105.6
Packed Height cm	113
Packed Width cm	79
Packed Depth cm	72

Available Options

Oil Pump

OP1	1 Oil Pump
OP2	2 Oil Pumps

Baskets

622_2_BASKETS	2 Baskets
622_3_BASKETS	3 Baskets
622_4_BASKETS	4 Baskets

Legs/Castors

OC200	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]
OC400	OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm